

FIRE TECHNOLOGY SERVICES

# **Confidential Report**

## Our Ref: 27/03978B/08/16

Notified Body for PPE Directive, Construction Products Regulation & Marine Equipment Directive I.D. No. 0338 & 0339 Fire Technology Services A division of BTTG T & C Ltd Wira House, West Park Ring Road, Leeds, LS16 6QL

Tel No: +44 (0)113 2591999



30 August 2016

BTTG Testing & Certification Ltd. Wira House West Park Ring Road Leeds, LS16 6QL England

> Tel: +44 (0)113 259 1999 Web:http://www.bttg.co.uk Email:CSLeeds@bttg.co.uk

Our Ref: 27/03978B/08/16 Your Ref:		Page 1 of 4
Client:	Camira Fabrics Meltham Mills Meltham West Yorkshire HD9 4AY	
Job Title:	Fire Test on One Sampl of Material	
Clients Order Ref:	57380	
Date of Receipt:	5 August 2016	
Description of Sample:	One sample of material, referenced: Lucia.	
Work Requested:	Fire Technology Services were requested to carry out the sample supplied to BS 476 Part 7 (stuck down).	a fire test on





BTTG Testing & Certification Ltd. Wira House West Park Ring Road Leeds, LS16 6QL England

> Tel: +44 (0)113 259 1999 Web:http://www.bttg.co.uk Email:CSLeeds@bttg.co.uk

30 August 2016

Page 2 of 4

Our Ref: 27/03978B/08/1627/03978B/08/16 Your Ref:

#### Camira Fabrics Ltd

## FIRE TESTS ACCORDING TO BS 476:PART 7:1987 (AS AMENDED) (Method for classification of the surface spread of flame of products)

#### Date of Test: 25/08/16

#### Conditioning

The sample was conditioned to constant mass at a temperature of  $23\pm2^{\circ}$ C and a relative humidity of  $50\pm10\%$  and maintained in this condition until required for testing

#### Procedure

The test was carried out in accordance with BS 476: Part 7: 1987(1993). The sponsor sampled the material and the specimens were cut from the sample to the dimensions set out in the standard by the sponsor. The specimens were tested stuck down onto 12mm calcium silicate board using Murabond Heavy Adhesive.

The following were recorded:-

- a) the time at which the flame front crosses each vertical reference line;
- b) the maximum extent of flame spread during the first 1.5 min from the start of the test;
- c) the maximum extent of flame spread during the whole test i.e. 10 min or less (if applicable)
- d) the time (and distance) at which maximum flame spread is reached.

The flame spread at 1.5min and the final flame spread results were compared with the standard class limits and a classification was assigned.

#### Requirements

The class limits for flamespread, detailed in BS 476:Part 7: are set out below.

	Flame spread at 1.5 min (mm)	Final flame spread (mm)			
Class 1	165 (+25)	165 (+25)			
Class 2	215 (+25)	455 (+45)			
Class 3	265 (+25)	710 (+75)			
Class 4	Exceeding Class 3 limits.				

A definitive classification is based on a sample of six specimens and the figure in brackets gives the tolerance by which only one specimen in six may exceed the class limit assigned.





BTTG Testing & Certification Ltd. Wira House West Park Ring Road Leeds, LS16 6QL England

> Tel: +44 (0)113 259 1999 Web:http://www.bttg.co.uk Email:CSLeeds@bttg.co.uk

30 August 2016

Page 3 of 4

Our Ref: 27/03978B/08/1627/03978B/08/16 Your Ref:

#### **Camira Fabrics Ltd**

#### Results

The test results relate only to the behaviour of the test specimens of the product under the particular conditions of test; they are not intended to be the sole criterion for assessing the potential fire hazard of the product in use.

Time for flame spread to reach (s) (mm)			Flame spread at 1.5 min (mm)	Maximum flame spread (mm)	Time to reach maximum flame spread (s)		
165	215	265	455	710	(1111)	()	
					65	65	60
					60	60	60
					60	60	60
					60	60	60
					60	60	60
					60	60	60

The results indicate that the sample met the performance requirements of Class 1.

#### Observations

--

Uncertainty of measurement has not been taken into account when presenting the test result. The relevant uncertainty value is included as an annex which forms an integral part of the report.

Reported by:	A Shute	A Shute, Fire Technician
Countersigned by:		P Doherty, Operational Head
	- A	

Enquiries concerning this report should be addressed to Customer Services.





BTTG Testing & Certification Ltd. Wira House West Park Ring Road Leeds, LS16 6QL England

> Tel: +44 (0)113 259 1999 Web:http://www.bttg.co.uk Email:CSLeeds@bttg.co.uk

30 August 2016

Page 4 of 4

Our Ref: 27/03978B/08/1627/03978B/08/16 Your Ref:

**Camira Fabrics Ltd** 

### **Uncertainty Budget - Annex**

The overall uncertainty budget for BS 476-7:1987 is as follows:-

Overall: ±20%

